

16 Step - 4000mm

Product Overview

Z/STEP/16STEP

VAT Not Included
Free Delivery

Step Width

500mm - Standard
850mm - Wide

Access Platform Options

Forward Access
Right Access
Left Access
Left & Right Access



Options

Rubber Wheels
RUGGED Wheels
Swing out Rear Stabilisers
Front Levelling Legs
Galvanize
Access Platform
Rear Safety Bar
Climb Prevention Bar
Bottom Gate
Basket

Mobile Steps lead time is generally 7 days. Whilst we stock the step components, the mobile steps are built to order. We would typically allow 3 days to build the steps, a day to paint them and then despatch the mobile ladders on a 3 day service.

Specification		
Dimensions	Standard Step Width (550mm)	Wide Step Width (850mm)
Platform Height From Ground	4000mm	4000mm
Overall Length	3140mm	3140mm
Overall Height	5000mm	5000mm
Frame Width	600mm	900mm
Overall Axle Width	1060mm	1360mm
Platform Size	550mm x 380mm	850mm x 380mm
Step Tread Width	550mm x 200mm	850mm x 200mm
Step Tread Vertical Spacing	250mm	250mm
Weight Standard Width	160kg	
Load Capacity	300kg	300kg

- These mobile safety steps are fabricated in one rigid structure giving good inherent strength
- Easy to manoeuvre with 2 large 200mm nylon wheels and 2 smaller 100mm wheels housed in swivel castors.
- The mobile ladder is fitted with our industrial hi-grip step as standard, also a 100mm kick-plate and safety operating sticker.
- Our 16 step mobile step is made and supplied in 2 parts with the bolts included. This is because the mobile steps are simply too big to put on a lorry and transport.
- Mobile steps are painted as standard using a one coat primer/finish - Zinfos 700CT, or can be galvanized.